

SUOER Fundus Camera (SW-8800): A compact device, high quality image, stereoscopic depth perception viewing, and the ability to capture a 65-degree angle of a single fundus photography without eye dilation, and Mosaic image of 128-degree

## Technical data

General	
Type of Photography	Color / Red-Free(Digital)
	IR(Digital) / Cobalt(Digital)
Angle of View	46.5°
Minimal Pupil Size	3.5 mm
Focus Adjustment Range	-25 to +25D
	(Without Compensation Lens)
Mosaic image (optional)	128°

Light Source	
Observation Light Source	Infrared LED
Flash Light Source	White LED
Eye Fixation Lamp	
Internal	LED Point, Orange
External	LED Point, Red
Working Distance	15 mm
Camera Resolution	10 Megapixels

7.0 inch Color LCD Monitor

Mount Movement	
Front and Back 85 mm	
Side to Side 110 mm	
Up and Down 30 mm	
Chin Rest Movement: 60 mm	

Electrical and Environmental	
Power Supply	100V to 240V AC, 50/60Hz,
	1 3 to 0 6A

Operating Environment		
Temperature	5 to 40°C	
Humidity	≤80%	
Atmospheric Pressure	700 hPa to 1060hPa	

Physical Characteristics		
	Dimensions (W x D x H):	430 x 450 x 570 mm
	Weight	Approximately 10Kg

Optional: FA, Mosaic

**Built-in Monitor**